



Timing



Scientific



IoT



Infrastructure



Telecommunication Network

Septentrio mosaic-T™ is a **multi-band, multi-constellation GNSS timing receiver** designed specifically for providing the highest security and availability for critical infrastructure and other applications where resilient timing is essential.

Mosaic-T™ is a low power surface-mount **module** with a wide array of interfaces including a dedicated timing input for time and frequency synchronization. It offers superior availability by tracking all Global Navigation Satellite System constellations (GNSS) and their current and future signals. With unique **built-in AIM+ technology** for anti-jamming, anti-spoofing and **interference mitigation**, Septentrio offers a highly resilient and precise timing receiver in a very small form factor.

KEY FEATURES

- ▶ **Accurate and resilient with dedicated timing features**
- ▶ **All-in-view satellite tracking: multi-constellation, multi-frequency**
- ▶ **Dedicated inputs for clock and frequency synchronisation**
- ▶ **Highly secure against jamming and spoofing with AIM+ unique interference mitigation technology**
- ▶ **Industry-leading ultra-low power consumption**
- ▶ **Easy-to-integrate**

BENEFITS

Top performance without compromises

The best of both worlds: small size with solid performance. Mosaic-T™ offers a high-precision solution for time and frequency synchronization under challenging conditions such as during GNSS jamming or spoofing. It offers unmatched resilience thanks to its all-constellation multi-frequency capabilities and AIM+ technology.

More compact than ever

Sized at only 31 x 31 x 4 mm and weighing no more than 7g, mosaic-T™ offers unparalleled size to performance ratio.

Meant for automated assembly

The mosaic-T™ module is designed for high volume automated assembly lines with minimal amount of additional components required. All interfaces, commands and data messages are fully documented. The complete RxTools software suite is also included with mosaic-T™. It enables quick and easy receiver configuration, data logging and analysis.

Advanced technologies inside

Septentrio's GNSS+ toolset enables accuracy and reliability in the toughest conditions with:

- ▶ **AIM+** the most advanced on-board interference mitigation technology on the market (mitigating both narrow and wide band chirp jammers).
- ▶ **LOCK+** for robust tracking despite mechanical shocks and vibrations.
- ▶ **APME+** multipath mitigation to distinguish direct signals from those reflected off nearby structures.
- ▶ **IONO+** provides advanced protection against ionospheric disturbances.

FEATURES

GNSS technology

448 hardware channels for simultaneous tracking of all visible supported satellite signals:

- ▶ GPS: L1C/A, L1PY, L2C, L2PY, L5
- ▶ GLONASS: L1CA, L2CA, L3 CDMA
- ▶ Beidou: B1I, B1C, B2a, B2I, B3
- ▶ Galileo: E1, E5a, E5b, E5 AltBoc
- ▶ QZSS: L1C/A, L2C, L5
- ▶ NavIC: L5
- ▶ SBAS: Egnos, WAAS, GAGAN, MSAS, SDCM (L1, L5)

Septentrio's patented GNSS+ technologies

- ▶ **AIM+** interference monitoring and mitigation (narrow band, wide band, chirp jammers)
- ▶ **IONO+** advanced scintillation mitigation
- ▶ **APME+** a posteriori multipath estimator for code and phase multipath mitigation
- ▶ **LOCK+** superior tracking robustness under heavy mechanical shocks or vibrations
- ▶ **RAIM+** receiver autonomous integrity monitoring
4 constellations

Protocols

Septentrio Binary Format (SBF)
NMEA 0183, v2.3, v3.03, V4.0

Interfaces

4 UART (LVTTTL, up to 4 Mbps)
Ethernet (RMII/MDIO), 10/100 Mbps
USB device (2.0, HS)
SDIO (mass storage)
2 GPIO user programmable
2 Event markers
1 Configurable PPS out⁴
Clock sync input
Frequency sync input (10 MHz)

PERFORMANCE

Time precision

xPPS out ⁴	5 ns
xPPS out with SBAS	2 ns
Event accuracy	< 20 ns

Positioning modes accuracy ^{1,2}

	Horizontal	Vertical
Standalone	1.2 m	1.9 m
SBAS	0.6 m	0.8 m

Velocity accuracy

3 cm/s

Maximum update rate

Position	10 Hz
----------	-------

Latency ³

<10 ms

Time to first fix

Cold start ⁵	< 45 s
Warm start ⁶	< 20 s
Re-acquisition	1 s

Tracking performance (C/N0 threshold)

Tracking	20 dB-Hz
Acquisition	33 dB-Hz

Firmware

Free product lifetime upgrades

PHYSICAL AND ENVIRONMENTAL

Package

Type	SMT solderable land grid array
Size	31 x 31 x 4 mm / 1.29 x 1.29 x 0.15 in
Weight	6.8 g / 0.24 oz

Electrical

Antenna pre-amplification range	15-50 dB
Antenna bias voltage	3.0-5.5 V
	Build-in current limit (150 mA)
Input voltage	3.3 VDC +/-5%
Power consumption	0.6 W typ 1.1 W max

Environmental

Operating temp	-40 to 85° C -40 to 185° F
Storage temp	-55 to 85° C -67 to 185° F

Humidity	5% - 95% (non-condensing)
----------	---------------------------

Vibration	MIL-STD-810G
-----------	--------------

Certification	CE, RoHS, WEEE
---------------	----------------



¹ Open sky conditions

² RMS levels

³ 99.9%

⁴ Incl. software compensation of sawtooth effect

⁵ No information available (no almanac, no approx position)

⁶ Ephemeris and approx. position known

EMEA (HQ)

Greenhill Campus
Interleuvenlaan 15i
3001 Leuven, Belgium

+32 16 30 08 00

septentrio.com

Americas

Suite 200
23848 Hawthorne Blvd
Torrance, CA 90505, USA

+1 310 541 8139

sales@septentrio.com

Asia-Pacific

Shanghai, China
Yokohama, Japan
Seoul, Korea

